

# FLIR Exx-Series



## Lightweight design, Heavyweight performers

The new user interface and new keypad make the new FLIR Exx-Series even more user-friendly than before. New features, such as MSX<sup>®</sup> and auto orientation, together with the Wi-Fi and MeterLink connectivity, ensure that the FLIR Exx-Series is the best in its class.

The cameras are ideal for predictive maintenance and planned inspections of electrical and mechanical systems to ensure they operate at maximum efficiency and safety with minimal energy consumption.

320  
x  
240

### Up to 320 x 240 pixels resolution

The FLIR Exx-Series infrared image resolution ranges from 160x120 pixels to 320x240 pixels depending on camera model. Every additional pixel means more valuable temperature information to isolate problem areas.



### Compact and lightweight

FLIR Exx-Series models weigh only 880g (battery included).



### High quality 3.1 Mpixel visual camera

Visible light camera makes observing and inspecting faster and easier.



### Thumbnail image gallery

An easy-to-access thumbnail image gallery helps you to quickly review and find your thermal images.



### ± 2% accuracy

High accuracy of ± 2% or ± 2 °C of reading.



### Intuitive user interface

Intuitive user interface including keypad and 3.5" touch screen.



### Built-in LED light

The built-in LED lamp ensures quality visual images regardless of job site lighting levels.



### Long life battery

With a 4 hour battery life, its easy-to-replace Lithium Ion batteries will keep up with your demanding schedule.



### Laser Pointer

A conveniently located button activates the laser pointer that will help you associate the hot or cold spot in the thermal image with the real physical target in the field.



### Picture-in-Picture (PiP)

With the PiP function it is easy to locate areas of interest.



### Text and voice annotations\*

Text comments can be made by using the touch screen. A headset can be connected to make voice annotations.



### Interchangeable lenses

In order to adapt the FLIR Exx-Series to every situation both wide angle and tele-lenses are available.



### Multi Spectral Dynamic Imaging (MSX<sup>®</sup>)

The innovative MSX<sup>®</sup> feature produces an image more rich in every detail than ever before.



### Auto orientation

The measurement data on the image will automatically adjust to the vertical or horizontal position of the camera.



### Multi Spectral Image storage

Combined image storage including MSX<sup>®</sup>, thermal, PiP and visual.

*\* Features dependant on camera model, please check technical specifications for more details.*



Connect to smartphone or tablet via Wi-Fi, using the FLIR Tools mobile app (Apple iOS and Android) for processing and sharing results as well as for remote control.

point and shoot



## FLIR Exx-Series camera model comparison

FLIR E40	FLIR E50	FLIR E60
		
Thermal image quality: 160x120 pixels	Thermal image quality: 240x180 pixels	Thermal image quality: 320x240 pixels
Thermal sensitivity: <0.07°C	Thermal sensitivity: <0.05°C	Thermal sensitivity: <0.05°C
Temperature range: -20°C to +650°C	Temperature range: -20°C to +650°C	Temperature range: -20°C to +650°C
Spot meters, areas and difference temperature	Spot meters, areas and difference temperature	Spot meters, areas and difference temperature
MeterLink™	MeterLink™	MeterLink™
Bluetooth® / WiFi	Bluetooth® / WiFi	Bluetooth® / WiFi
2x digital zoom	2x, 4x digital zoom	2x, 4x digital zoom
MSX®	MSX®	MSX®
Multi spectral image storage	Multi spectral image storage	Multi spectral image storage
PiP IR area on visual image	PiP Scalable IR area on visual image	PiP Scalable IR area on visual image
Video out	Video out	Video out
Non-radiometric IR-video recording	Non-radiometric IR-video recording	Non-radiometric IR-video recording
Non-radiometric IR-video streaming	Non-radiometric IR-video streaming	Non-radiometric IR-video streaming
Radiometric IR-video streaming	Radiometric IR-video streaming	Radiometric IR-video streaming



Mechanical check-up of an electrical motor using the FLIR Exx-Series. The Auto orientation feature automatically adjusts the measurement information on the display to the position of the camera.



# FLIR Exx-Series

## Technical specifications

### Camera specific



FLIR E40



FLIR E50



FLIR E60

	FLIR E40	FLIR E50	FLIR E60
<b>Imaging Performance</b>			
IR resolution	160 × 120 pixels	240 × 180 pixels	320 × 240 pixels
Spatial resolution	2.72 mrad	1.82 mrad	1.36 mrad
Thermal sensitivity	< 0.07 °C	< 0.05 °C	< 0.05 °C
Zoom	2x digital zoom	2x, 4x digital zoom	2x, 4x digital zoom
<b>Image presentation</b>			
Picture in Picture	IR area on visual image	Scalable IR area on visual image	Scalable IR area on visual image
Image modes	IR image, visual image, thumbnail gallery, picture-in-picture	IR image, visual image, picture-in-picture, thumbnail gallery	IR image, visual image, picture-in-picture, thumbnail gallery

### General

<b>Imaging Performance</b>	
FOV / Minimum focus distance	25° × 19° / 0.4 m
Spectral range	7.5–13 μm
Image frequency	60 Hz
Focus	Manual
Focal Plane Array (FPA)	Uncooled microbolometer
<b>Image presentation</b>	
Auto orientation	Automatic adjustment of measurement data (vertical/horizontal)
Display	Built-in 3.5" LCD touch screen, 320 × 240 pixels
<b>Digital camera</b>	
Built-in digital camera	3.1 Mpixels, and one LED light
<b>Image annotations</b>	
Voice	60 seconds via Bluetooth®
Text	Text from predefined list or soft keyboard on touch screen
MeterLink	Possible to connect, via Bluetooth, Extech Moisture meter M0297 or Extech clamp meter EX845
<b>Measurement</b>	
Object temperature range	–20°C to +120 °C / 0°C to +650 °C
Accuracy	±2 °C or ±2% of reading
<b>Measurement analysis</b>	
Spotmeter	3
Area	3 boxes with min./max./average
Difference temperature	Delta temperature between measurement functions or reference temperature
Automatic hot/cold detection	Auto hot or cold spotmeter markers within area
Emissivity correction	Variable from 0.01 to 1.0 or selected from list of materials
Measurement corrections	Reflected temperature, optics transmission and atmospheric transmission
Color alarm	Red above, Blue below and Yellow interval
<b>Set-up</b>	
Image controls	Palettes (Arctic, Gray, Iron, Lava, Rainbow and Rainbow HC), image adjustment (auto/manual)
Set-up controls	Local adaptation of units, language, date and time formats; automatic shutdown, display intensity

#### Laser pointer

Laser alignment	Position is displayed on the IR image
Laser	Activated by dedicated button

#### Image storage

Format	Standard JPEG - including measurement data on SD memory card
Mode	Simultaneous storage of images in IR, visual and MSX

#### Video streaming/recording

Non-radiometric IR-video recording	MPEG4 to memory card
Non-radiometric IR-video streaming	Uncompressed colorized video using USB
Radiometric IR-video streaming	Full dynamic to PC using USB

#### Power

Battery type	Lithium-Ion (field replaceable) - 4 hours operating time
Charging system	In camera, AC adaptor, 2-bay charger or 12 V from a vehicle
Power management	Automatic shutdown and sleep mode (user selectable)
AC operation	AC adaptor, 90-260 V AC
Adaptor voltage	12 V output to camera

#### Environmental specifications

Operating temperature range	-15 to +50 °C
Storage temperature range	-40 to +70 °C
Humidity	IEC 60068-2-30/24 h 95% relative humidity +25 °C to +40 °C / 2 cycles
Drop	2 m
Shock / Vibration	25 g (IEC 60068-2-29) / 2 g (IEC 60068-2-6)

#### Data communication interfaces

Interfaces	USB-mini, USB-A, Composite video
USB	USB-A: Connect external USB device - USB-mini-B: Data transfer to and from PC / Streaming MPEG 4
Bluetooth®, WiFi	Yes

#### Report generation

FLIR Tools	Flir Tools™ Software specifically designed to provide an easy way to create inspection reports. Available on the major platforms: Android, Windows, MacOS and iOS.
------------	--

#### Physical characteristics

Camera weight, incl. battery	0.88 kg
Camera size (L x W x H)	246 x 97 x 184 mm
Shipping size	500 x 350 x 190 mm
Shipping weight	4.7 kg

#### Standard package

FLIR E40, FLIR E50 or FLIR E60: Hard transport case, Thermal imaging camera with lens, Battery charger, Battery (2 ea.), Hand strap, FLIR Tools™ download card, Memory card, Lens cap, Power supply incl. multiplugs, USB cable, User documentation CD-ROM, Video cable, Battery charger, Printed documentation